

Large Screw Pin Bow Shackle

- Meets the W.L.L performance requirements of the withdrawn standard BS 3032.
- High tensile steel C1045.
- Self colour and hot dip galvanised finish available.
- Supplied with an EC declaration of conformity.
- Factor or safety 4:1.
- Marked with manufacturers mark, ID mark, W.L.L & CE.



W.L.L	a	b	c	d	e	Weight
tonnes	(inches)	(inches)	(inches)	(inches)	(inches)	kgs
0.45	3/8	1/2	5/8	1 5/8	1	0.18
0.75	1/2	5/8	7/8	2 1/8	1 1/4	0.34
1.25	5/8	3/4	1 1/8	2 3/4	1 1/2	0.65
2.00	3/4	7/8	1 3/8	3 3/8	1 3/4	1.08
2.75	7/8	1	1 5/8	3 7/8	2	1.80
3.75	1	1 1/8	1 3/4	4 1/4	2 1/4	2.46
4.75	1 1/8	1 1/4	2	4 7/8	2 1/2	3.47
5.75	1 1/4	1 3/8	2 1/4	5 3/8	2 3/4	4.56
7.25	1 3/8	1 1/2	2 1/2	6	3	6.07
8.50	1 1/2	1 3/4	2 3/4	6 5/8	3 1/2	8.35
9.50	1 5/8	1 7/8	3	7 3/8	3 3/4	11.81
11.50	1 3/4	2	3 3/8	8 1/8	-	13.17